

2012 CONSUMER & TRADE GUIDES

2012 Consumer and Trade Guides are now available.

The 2012 Spinlock Guides features full product descriptions along with full technical details, load holding graphs, drawings, measurements, whilst the Trade Guides are larger and more comprehensive in detail.




NEW ZR1014 JAWS

ZR1014 Jammers are now being supplied with a new jaw profile. Changes include a more defined anodised jaw surface and a PTFE bearing strip on the lower jaw which is profiled to move dirt away from it's surface and remain lubricated for longer. New instructions also highlight more clearly the need for a near perfect line lead into the ZR1014. Any existing customers with ZR1014 Jammers are entitled to a free jaw upgrade.



XX0812 POWERCLUTCH ROLLER CAGES

When cleaning, maintaining or fitting new roller cages in the XX0812 Powerclutches, it is important the roller cage is placed back on the jaw set the correct way round. Marked with an arrow on the side of the roller cage, it is essential that this faces forward towards the front of the jaw set.



NEW BE BULLS EYE WITH TWIN FIXINGS

Our popular BE Bulls Eye leads are now available with twin fixings. Enjoying the same low profile design with sealing gasket, the new twin fixing Bulls Eye are available in 10,12 and 16mm versions for both OEM and Retail customers.

BE10/TF, BE12/TF and BE16/TF



ZERO NOW AVAILABLE IN SIZE 4

The ZERO Sports Flotation Vest is now available in a Size 4, DW-BAM/4. Size 4 suits chest sizes 125cm - 135cm

Customers are reminded that the ZERO is designed to be stretch fit, close fitting with the shaped panels and a body fit system and ensuring a streamlined fit.



TILLER EXTENSION COLOURS

Please note that the Tiller Extension colour known as 'Graphite' has now changed to description 'Bronze'. Please amend your prices lists, websites and printed materials descriptions. Product codes will remain the same.



WWW.SPINLOCK.CO.UK/PORTAL

To download the latest Spinlock Images, Videos, Press Releases & Printed Materials